

# 8620 & 8670 Rocker Switches - 3 Positions 10A 250Vac



- ▶ 3 position miniature rocker switch
- ▶ Ratings up to 15A, 250Vac
- ▶ Single & double pole
- ▶ Centre off switching
- ▶ Push on, solder and PCB terminals
- ▶ Matching indicators
- ▶ Panel cut out:  
single: 19.3 x 12.9  
double: 19.3 x 21.9

H8620VB ---  
T8620VB ---

H8670VB ---  
T8670VB ---

## Approvals and specifications



10(4)A 250Vac T90



UL CSA 15A 277Vac (Single pole)  
UL CSA 250Vac 1/2hp (Single pole)  
UL CSA 125Vac 1/4hp (Single pole)  
UL CSA 10A 277Vac (Double pole)  
UL CSA 277Vac 1/2hp (Single & Double pole)  
UL 90°C, file E45221, CSA file LR10990

μ contact gap.  
Technical data on pages 4 & 5.


**H 8620 V B - - -**

TERMINAL FUNCTION ROCKER BODY PRINT, COLOUR, ETC


▶ TERMINAL	▶ FUNCTION	▶ ROCKER	▶ BODY	▶ OPTIONS
<b>H</b>  4.8 x 0.8	 <b>8620</b> ON - OFF - ON Single pole	<b>V</b> Curved  <b>H</b> Slotted for actuator (8620 only) 	<b>B</b> Single pole  12.9 Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 15.0 Dim X 19.1/19.2 19.3/19.4 19.7/19.8 21.0	<b>Finish</b> Matt finish only. <b>Colour</b> Call sales for custom colours. A full range is available for large orders. <b>Legend printing</b> Select from the examples or call sales for custom legend. <b>Protective covers IP65</b> <b>L167 for SP</b> <b>L180 for DP</b> Snaps on to body, this reduces panel thickness by 0.8mm.
<b>T</b>  Ø2.15 6.4 Solder	 <b>8670</b> ON - OFF - ON Double pole		<b>B</b> Double pole  21.9 Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 24.0 Dim X 19.1/19.2 19.3/19.4 19.7/19.8 21.0	
<b>X</b>  4.0 8.0 PCB 0.8sq Double pole switches with X terminals are supplied without terminal barriers			Cut-outs must be punched in the direction of insertion	

## Dimensions (mm)


**8620VB** (H terminals shown)



**8670VB** (H terminals shown)



**8670VB** (X terminals shown)



CL141



CL142